

DATI ELETTRICI 4WMU2W - 60Hz

Type	P ₂ [Hp]	P ₂ [kW]	Voltage [V]	S.F.	Ph	FULL LOAD AMPS	FULL S.F. AMPS	rpm	η [%]	Capacitor [μF]	Thrust Load		Length A		Weight		Cable Length		Cable Section [AWG]
						I _n [A]	I _{MAX} [A]				[lbf]	[N]	[mm]	[in]	[kg]	[lb]	[m]	[ft]	
						Single-phase 2-wire PSC													
4WMU2W-S050	1/2	0.37	115	1.6	1	7.2	9.1	3450	54	35	450	2000	357	14.1	10.7	23.6	1.7	5 1/2	3 x 14
4WMU2W-S050	1/2	0.37	230	1.6	1	3.1	4	3450	54	20	450	2000	357	14.1	10.7	23.6	1.7	5 1/2	3 x 14
4WMU2W-S075	3/4	0.55	115	1.5	1	9.8	10.4	3450	61	35	450	2000	377	14.8	11.3	24.9	1.7	5 1/2	3 x 14
4WMU2W-S075	3/4	0.55	230	1.5	1	4.1	5.4	3450	61	20	450	2000	377	14.8	11.3	24.9	1.7	5 1/2	3 x 14
4WMU2W-S100	1	0.75	230	1.4	1	5.7	7.1	3450	61	35	450	3000	397	15.6	11.9	26.2	1.7	5 1/2	3 x 14
4WMU2W-S150	1.5	1.1	230	1.3	1	7.9	9.6	3450	62	35	700	3000	422	16.6	12.7	28.0	1.7	5 1/2	3 x 14